

CHARACTERISTICS

Simple and essential parallel sliding system with a special modular frame structure that allows for the construction of multiple types. Multicanal guides facilitate the collection of all panels adjacent to the first, thus allowing the opening of a large part of the surface. Stainless steel accessories ensure stability and durability over time.



MULTICANAL
GUIDES



STAINLESS
STEEL



MINIMAL
PROFILE



CENTRAL NODE
26 MM

S.78

MINIMAL SLIDING DOOR

S.78

ALUMINIUM SYSTEM


NUMBER OF TRACKS	2/3
DIMENSIONS OF CENTRAL NODE	26 mm
MAXIMUM PANEL WIDTH	2400 mm
MAXIMUM PANEL HEIGHT	3000 mm
MAXIMUM PANEL WEIGHT	240 Kg
WEIGHT OF GLAZED UNIT	8-10 Kg/m ² excluding glazing
THERMAL INSULATED PROFILES	NO
PANEL ADJUSTMENTS	✓
SLIDING	BOTTOM
SLIDING ACCESSORIES	STAINLESS STEEL
HEIGHT OF BOTTOM TRACK	25 mm
RECESSED TRACK	UPON REQUEST
COLOUR OF ACCESSORIES	BLACK SILVER
CLOSURES	SIDE ON FRAME
OPENING FROM OUTSIDE WITH A KEY	UPON REQUEST
RIGHT / LEFT PACKING	✓
SLIDING CORNER TYPE	✓
GLAZING	8/11 mm 24/30 mm
WATER TIGHTNESS CERTIFICATION EN 1027 - EN 12208	CLASS 6A
AIR PERMEABILITY CERTIFICATION EN 1026 - EN 12207	CLASS 3
WIND RESISTANCE CERTIFICATION EN 12211 - EN 12210	CLASS 2A

OPENING MODULE SET UP


2 PANELS 2 TRACKS - LEFT INTERNAL PANEL



2 PANELS 2 TRACKS - RIGHT INTERNAL PANEL




3 PANELS 3 TRACKS - LEFT INTERNAL PANEL




3 PANELS 3 TRACKS - RIGHT INTERNAL PANEL




4 PANELS 2 TRACKS - CENTRAL INTERLOCK




6 PANELS 3 TRACKS - CENTRAL INTERLOCK



5 PANELS 3 TRACKS - CENTRAL INTERLOCK



5 PANELS 3 TRACKS - CENTRAL INTERLOCK



For finishes, visit the website sunroom.it

The view is considered to be from the inside. For good operation of the glazed unit, always follow the type indicated.